




Setup - 4R

v 18.1

	100cc	L 206	
Axle	C 3.2	C 3.2 / 1.5	C 3.2 / C 1.5
Rear Hubs	L. 95 (Al)	L. 95 (Al)	L. 95 (Al)
Front Hubs	L. 60/76 (Al)	L. 60/76 (Al)	L. 76 (Mg)
Ackermann Col.	Center	Center	Center / Low
Ackermann Stub	Pos. 1	Pos. 1 / 2	Pos. 1
Toe	+ 2mm	0	+ 4-6mm
Caster / Eccentric	.5 + 0	1.3/1.8+ 0	2.3 + 0
Front Width	116 - 117	116 - 117	118- 119
Rear Width	138.5 - 140	137 - 139	136
Wheel Set	DF - 130 x 130	DF- 130 x 210/180	Al - 130 x 180
Ride Height (R)	Center	Center / Low	Center
Ride Height (F)	Center	Center/Low	Center / High

*Measurements are in Metric

Its possible to loosen the lower seat bolts and even mount the lower seat in the center point only, also, in grippy conditions try removing the center floor tray bolts for improved flex for the L206. In both categories test a shorter axle - 1020/ 1000 long.



J3 COMPETITION
2154 NORCROSS ROAD
ERIE PENNSYLVANIA USA 16510
+1.814.864.1846